

### Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**Product name:** UP2811, UP2812 2K SYSTEM 20 CLEAR COAT HS

**Product code:** S2081

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Use of substance / mixture:** PAINT PRODUCT CONTAINING MIXTURE OF SOLVENTS

#### 1.3. Details of the supplier of the safety data sheet

**Company name:** U-POL US Inc.

630 Selvaggio Drive

Suite 300

Nazareth

PA 18064

USA

**Tel:** 1-800-340-7824

**Fax:** 1-800-787-5150

**Email:** technical:u-pol.com

#### 1.4. Emergency telephone number

**Emergency tel:** 1-800-424-9300 (CHEMTREC)

### Section 2: Hazards identification

#### 2.1. Classification of the substance or mixture

**Classification under CHIP:** -: R10; Xn: R20/21; Xi: R38; -: R52/53

**Most important adverse effects:** Flammable. Harmful by inhalation and in contact with skin. Irritating to skin. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**Classification under CLP:** This product has no classification under CLP.

#### 2.2. Label elements

**Label elements under CHIP:**

**Hazard symbols:** Harmful.



**Risk phrases:** R10: Flammable.

R20/21: Harmful by inhalation and in contact with skin.

R38: Irritating to skin.

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

## SAFETY DATA SHEET

UP2811, UP2812 2K SYSTEM 20 CLEAR COAT HS

Page: 2

**Safety phrases:** S16: Keep away from sources of ignition - No smoking.

S23: Do not breathe vapour/spray

S36/37: Wear suitable protective clothing and gloves.

**Precautionary phrases:** Restricted to professional users.

### 2.3. Other hazards

**Other hazards:** Harmful: may cause lung damage if swallowed.

**PBT:** This substance is not identified as a PBT substance.

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

#### Hazardous ingredients:

##### XYLENE

EINECS	CAS	CHIP Classification	CLP Classification	Percent
215-535-7	1330-20-7	-: R10; Xn: R20/21; Xi: R38	Flam. Liq. 3: H226; Acute Tox. 4: H332; Acute Tox. 4: H312; Skin Irrit. 2: H315	10-30%

##### N-BUTYL ACETATE

204-658-1	123-86-4	-: R10; -: R66; -: R67	Flam. Liq. 3: H226; STOT SE 3: H336; -: EUH066	1-10%
-----------	----------	------------------------	---	-------

##### 4-METHYLPENTAN-2-ONE

203-550-1	108-10-1	F: R11; Xn: R20; Xi: R36/37; -: R66	Flam. Liq. 2: H225; Acute Tox. 4: H332; Eye Irrit. 2: H319; STOT SE 3: H335; -: EUH066	1-10%
-----------	----------	-------------------------------------	--	-------

##### 2-METHOXY-1-METHYLETHYL ACETATE

203-603-9	108-65-6	-: R10	Flam. Liq. 3: H226	1-10%
-----------	----------	--------	--------------------	-------

##### LOW BOILING POINT NAPHTHA - UNSPECIFIED - SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.

265-199-0	64742-95-6	Xn: R65; -: R10; Xi: R37; N: R51/53	Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT SE 3: H335; Aquatic Chronic 2: H411	1-10%
-----------	------------	--	---	-------

## Section 4: First aid measures

### 4.1. Description of first aid measures

**Skin contact:** Wash immediately with plenty of soap and water. Remove all contaminated clothes and footwear immediately unless stuck to skin.

**Eye contact:** Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

**Ingestion:** Do not induce vomiting. Wash out mouth with water. Transfer to hospital as soon as possible.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so.

[cont...]

## SAFETY DATA SHEET

UP2811, UP2812 2K SYSTEM 20 CLEAR COAT HS

Page: 3

### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and pain.

**Ingestion:** There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Drowsiness or mental confusion may occur.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

### 4.3. Indication of any immediate medical attention and special treatment needed

**Immediate / special treatment:** Not applicable.

## Section 5: Fire-fighting measures

### 5.1. Extinguishing media

**Extinguishing media:** Carbon dioxide. Dry chemical powder. Alcohol or polymer foam.

### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** Flammable. In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

### 5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear self-contained breathing apparatus.

## Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Refer to section 8 of SDS for personal protection details.

### 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding. Alert the neighbourhood to the presence of fumes or gas.

### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Absorb into dry earth or sand. Wash the spillage site with large amounts of water.

### 6.4. Reference to other sections

**Reference to other sections:** Refer to section 8 of SDS.

## Section 7: Handling and storage

### 7.1. Precautions for safe handling

**Handling requirements:** Ensure there is sufficient ventilation of the area. Smoking is forbidden.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in cool, well ventilated area. Keep away from sources of ignition. Keep container tightly closed. Keep away from direct sunlight.

[cont...]

## SAFETY DATA SHEET

UP2811, UP2812 2K SYSTEM 20 CLEAR COAT HS

Page: 4

**Suitable packaging:** Must only be kept in original packaging.

### 7.3. Specific end use(s)

**Specific end use(s):** No data available.

## Section 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Workplace exposure limits:

#### Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	50 ppm	100 ppm	1 mg/m <sup>3</sup>	-

#### Hazardous ingredients:

##### XYLENE

#### Workplace exposure limits:

#### Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	220 mg/m <sup>3</sup>	441 mg/m <sup>3</sup>	-	-

##### N-BUTYL ACETATE

UK	724 mg/m <sup>3</sup>	966 mg/m <sup>3</sup>	-	-
----	-----------------------	-----------------------	---	---

##### 4-METHYLPENTAN-2-ONE

UK	208 mg/m <sup>3</sup>	416 mg/m <sup>3</sup>	-	-
----	-----------------------	-----------------------	---	---

##### 2-METHOXY-1-METHYLETHYL ACETATE

UK	274 mg/m <sup>3</sup>	548 mg/m <sup>3</sup>	-	-
----	-----------------------	-----------------------	---	---

### 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

**Respiratory protection:** Compressed airline breathing apparatus (EN139).

**Hand protection:** Nitrile gloves.

**Eye protection:** Face-shield.

**Skin protection:** Protective clothing with elasticated cuffs and closed neck.

## Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

**State:** Liquid

**Colour:** Colourless

**Odour:** Aromatic

**Evaporation rate:** Moderate

**Oxidising:** Non-oxidising (by EC criteria)

**Solubility in water:** Insoluble

[cont...]

## SAFETY DATA SHEET

UP2811, UP2812 2K SYSTEM 20 CLEAR COAT HS

Page: 5

**Also soluble in:** Most organic solvents.

**Viscosity:** Viscous

**Kinematic viscosity:** 40 secs

**Viscosity test method:** DIN 4 Cup 20C

**Flammability limits %:** lower: 1.0

**upper:** 6.6

**Flash point°C:** 24

**Autoflammability°C:** 490

**Relative density:** 0.96

**VOC g/l:** 515 (4.33 lb/gal)

### 9.2. Other information

**Other information:** Not applicable.

## Section 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity:** Stable under recommended transport or storage conditions.

### 10.2. Chemical stability

**Chemical stability:** Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

**Hazardous reactions:** Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

### 10.4. Conditions to avoid

**Conditions to avoid:** Direct sunlight. Heat. Sources of ignition. Flames.

### 10.5. Incompatible materials

### 10.6. Hazardous decomposition products

**Haz. decomp. products:** In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

## Section 11: Toxicological information

### 11.1. Information on toxicological effects

**Relevant effects for mixture:**

Effect	Route	Basis
Acute toxicity (harmful)	INH DRM	Hazardous: calculated
Irritation	DRM	Hazardous: calculated

### Symptoms / routes of exposure

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and pain.

**Ingestion:** There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Drowsiness or mental confusion may occur.

[cont...]

## SAFETY DATA SHEET

UP2811, UP2812 2K SYSTEM 20 CLEAR COAT HS

Page: 6

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

### Section 12: Ecological information

#### 12.1. Toxicity

**Ecotoxicity values:** Not applicable.

#### 12.2. Persistence and degradability

**Persistence and degradability:** Not biodegradable.

#### 12.3. Bioaccumulative potential

**Bioaccumulative potential:** No data available.

#### 12.4. Mobility in soil

**Mobility:** Volatile. Heavier than water.

#### 12.5. Results of PBT and vPvB assessment

**PBT identification:** This substance is not identified as a PBT substance.

#### 12.6. Other adverse effects

**Other adverse effects:** No data available.

### Section 13: Disposal considerations

#### 13.1. Waste treatment methods

**Disposal operations:** Incineration on land.

**Recovery operations:** Use principally as a fuel or other means to generate energy.

**Disposal of packaging:** Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

### Section 14: Transport information

#### 14.1. UN number

**UN number:** UN1263

#### 14.2. UN proper shipping name

**Shipping name:** PAINT RELATED MATERIAL

#### 14.3. Transport hazard class(es)

**Transport class:** 3

#### 14.4. Packing group

**Packing group:** III

#### 14.5. Environmental hazards

**Environmentally hazardous:** No

**Marine pollutant:** No

[cont...]

## SAFETY DATA SHEET

UP2811, UP2812 2K SYSTEM 20 CLEAR COAT HS

Page: 7

### 14.6. Special precautions for user

**Special precautions:** No special precautions.

**Tunnel code:** D/E

**Transport category:** 3

## Section 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### 15.2. Chemical Safety Assessment

**Chemical safety assessment:** A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

## Section 16: Other information

### Other information

**Other information:** This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

FOR PROFESSIONAL USE ONLY. Read full instructions before use.

IMPORTANT: This product contains hazardous materials and therefore appropriate personal protective equipment should always be used.

Please refer to the label and consult the material safety data sheet for full handling instructions and personal protection information. These are available via your local stockist or via the U-POL website at [WWW.U-POL.COM](http://WWW.U-POL.COM).

U-POL disclaim any liability where the user does not wear the recommended personal protective equipment.

**Phrases used in s.2 and 3:** EUH066: Repeated exposure may cause skin dryness or cracking.

H225: Highly flammable liquid and vapour.

H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H312: Harmful in contact with skin.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H335: May cause respiratory irritation.

H336: May cause drowsiness or dizziness.

H340: May cause genetic defects <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H350: May cause cancer <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H411: Toxic to aquatic life with long lasting effects.

R10: Flammable.

[cont...]

## SAFETY DATA SHEET

UP2811, UP2812 2K SYSTEM 20 CLEAR COAT HS

Page: 8

R11: Highly flammable.

R20/21: Harmful by inhalation and in contact with skin.

R20: Harmful by inhalation.

R36/37: Irritating to eyes and respiratory system.

R37: Irritating to respiratory system.

R38: Irritating to skin.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65: Harmful: may cause lung damage if swallowed.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. Addition of reducers, hardeners and other additives over and above U-POL's recommendations for use, may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, this company shall not be held liable for any damage resulting from handling or from contact with the above product.